

제품명	Refrigerated/Heating Circulators RCHM8
제품그룹	CHILLER
제품키워드	Refrigerated/Heating Circulators



제품상세

CPT Order No : 910019

Model : **RCHM8**

Filling volume : 8 liters

Working temp. range : -20.00℃~+100.00℃

- Temperature setting to 0.01℃
- Temp. stability / Temp. uniformity : ±0.01℃ / ±0.01℃
- Temp. controller : PID temperature control

Heat cap. : 1000W

Cooling capacity W (Bath fluid : Ethanol)20℃ : 250W

Order Made : ①External PT100 sensor

②RS232 interface

③Refrigerated unit / solenoid valve

Pump capacity Flow rate : 25 l/min

Pressure : 0.6 bar

Pump In/Out : 12.7Ø

Bath opening/Filling bath depth volume(W×D×H)(cm):17×17.5×15

Dimensions(W×D×H)(cm) : 22×39×59

Weight : 27 kg



CPT INC. <http://www.cpt.kr>

TEL: 82-31-454-1735 FAX: 82-31-454-8693

E-mail : cpt1287@nate.com

Refrigerated/Heating Circulators 정밀용 저온순환수조 RCHM8

- Multi display (LED) with resolution 0.1(Temp.-Setting indication)
- Early warning system for low and high temperature limits
- Built in with automatic adjustable shut off overheat protection.
- Excellent safety with waterless automatic shut off overheat protection.
- Safety apparatus for the electric leakage and excess
- Alarm setting function for temperature and time

Application Area

- External temperature control applications to
 - *Calibration Baths *Measuring cells *Fomenters *Electrophoresis chambers *Polari meters
 - * Chromatography columns *Photometers *Rotary evaporators *Viscometers
- External PT100 sensor CPT Order No:710007 and 13
- Pump In /Out : 12.7Ø
- Temp. controller : PID temperature control
- Cooling capacity test (Bath fluid : Ethanol)
- RCHM Model connections Application (Page: 4,5,6)
- Temperature setting to 0.01°C
- Temp. stability / Temp. uniformity : $\pm 0.01^{\circ}\text{C}$ / $\pm 0.01^{\circ}\text{C}$

CPT Order No	CPT Model	Working Temp Range °C	Temp Stab °C	Heat Cap W	Cooling capacity W (Bath fluid: Ethanol) 20 °C	Pump capacity Flow rate/Pressure l/min. bar	Bath opening bath depth W×D×H cm	Fill. vol. liters	Dimensions W*D*H cm	Weight kg
910019	RCHM8	-20.00~100.00	± 0.01	1000	250	25 0.6	17*17.5*15	8	22*39*59	27

Dimensions External features of size (mm)

